


TECHNICAL SPECIFICATION

CODE	AP 123
DESCRIPTION	PURLIN MOUNT ANCHOR
SPECIFICATION SUMMARY	The LOW-PRO Purlin Mount Anchor installed through metal deck into purlin for fall arrest or rope access use. System design, supply, layout, installation and certification by a SAYFA approved installer, as per the manufacturer's installation instructions and current standards.

TECHNICAL DATA	<p>RATING</p> <ul style="list-style-type: none">- Fall arrest - 15kN- Rope access - 12kN <p>MATERIALS</p> <ul style="list-style-type: none">- Anchor assembly - 316 stainless steel- Penetration seal - EPDM rubber <p>DIMENSIONS</p> <ul style="list-style-type: none">- Total length - 165mm- Eyebolt - diameter 60mm OD, 35mm ID- Threaded rod - M16 x 100mm- Flange - 70mm
----------------	--

- SUBSTRUCTURE REQUIREMENTS**
- Minimum purlin size - 150 x 1.5mm
 - Minimum roof deck thickness - 0.42mm
 - Minimum of 3 purlins connected to roof deck
 - Less than 5 purlins requires roof to be fastened to roof deck
 - Rope access use requires 2 x 14g self-drilling screws through the roof sheet into the purlin on which the anchor is attached and to the purlin above or below the anchor

(Refer installation manual)



COMPLIANCE	The LOW-PRO Purlin Mount Anchor is designed and manufactured in accordance with requirements of Australian Standards AS/NZS 1891.4:2009 and AS/NZS 5532:2013 and relevant statutory OHS Codes of Practice/Guidelines.
------------	---


TESTING	<p>Testing and performance based on requirements of Australian Standard AS/NZS 5532:2013. (Connected to minimum support structure).</p> <ul style="list-style-type: none">- Dynamic load test - 15kN- Static load test - 15kN
---------	--

PRODUCT WARRANTY	10 years from date of purchase subject to correct installation, use and maintenance in accordance with manufacturer's specifications and recommendations.
------------------	---

INSPECTION AND MAINTENANCE	<p>Inspection and certification required every 12 months by competent height safety system inspector in accordance with manufacturer's specifications and requirements of Australian Standard AS/NZS 1891.4:2009 Section (9).</p> <p>(Refer operation manual).</p>
----------------------------	--

IMPORTANT NOTE	Failure to supply and/or install proprietary product in accordance with above standards and codes, specifications and instructions voids complete system certification and/or warranty.
----------------	---

PRODUCT DISCLAIMER LINK	HTTPS://SAYFA.COM.AU/WP-CONTENT/UPLOADED/2019/07/PRODUCT-DISCLAIMER_02.07.2019_SS.PDF
-------------------------	--



AP 123F PURLIN MOUNT ANCHOR



AP 123C PURLIN MOUNT ANCHOR



AP 123S PURLIN MOUNT ANCHOR

Designed and manufactured by Sayfa Group. For all technical assistance contact Sayfa Group. SAYFAGROUP-07.06.2021

